

Mitel Phone Installation Guide

FEBRUARY 2021

Release 1.0

2924-001



NOTICE

The information contained in this document is believed to be accurate in all respects but is not warranted by Clearspan LLC (Clearspan®). The information is subject to change without notice and should not be construed in any way as a commitment by Clearspan or any of its affiliates or subsidiaries. Clearspan and its affiliates and subsidiaries assume no responsibility for any errors or omissions in this document. Revisions of this document or new editions of it may be issued to incorporate such changes.

No part of this document can be reproduced or transmitted in any form or by any means - electronic or mechanical - for any purpose without written permission from Clearspan LLC.

TRADEMARKS

The trademarks, service marks, logos and graphics (collectively "Trademarks") appearing on Clearspan's Internet sites or in its publications are registered and unregistered trademarks of Clearspan LLC. Use of the Trademarks is prohibited without the express consent from Clearspan.

Mitel Phone Installation Guide
Release #1.0 February 2021

®,™ Trademark of Clearspan LLC
© Copyright 2021 Clearspan LLC
All rights reserved

REVISION HISTORY..... 1

OVERVIEW..... 2

INSTALLATION 3

ADDITIONAL PROCEDURES 6

 Restarting Phones..... 6

 Factory Defaulting Phones..... 8

REVISION HISTORY

The following table represents the revision history of this publication:

REVISION	DATE COMPLETED	POINT OF CONTACT	AFFECTED SECTIONS
1	02/2021	Clearspan Technical Publications	All





OVERVIEW


This document provides the steps to install the Mitel 6800 and 6900 series phones that have been provisioned for the Clearspan System.

Before Installation, you must configure the Phone Type in Clearspan, and the User and Device, in OpEasy.

INSTALLATION

The following table lists the Mitel Phone installation steps, and the expected results:

	ACTION	EXPECTED RESULTS
Create Users and Devices		
1	Create a User and Assign the Mitel Phone to the User.	
2	Start with a Factory Defaulted Phone.	
Determine the IP Address of the Mitel 6863i and 6865i Phones		
3	Press the Option Key. 	The Options List is displayed.
4	Using the Navigation/Select Keys.  Scroll down to Phone Status option. Select the option.	The Phone Status page is displayed.
5	Scroll down to the IP and MAC Address option. Select the option	The IP Address is displayed.
Determine IP Address of the Mitel 6867i, 6869i, 6920 and 6930 Phones		
6	Press the Option Key. 	The Settings screen is displayed. The Status is highlighted.
7	Press Select .	The Status page is displayed.
8	Using the Navigation/Select Keys  Scroll down to Network .	The IP Address is displayed.





Determine IP Address of the Mitel 6873i and 6940 Phones		
9	<p>Press the Option Key</p> 	The Settings screen is displayed.
10	Touch Status .	The Status page is displayed.
11	Touch Network .	The IP Address is displayed.
Phone Configuration if DHCP Server Address is not available. If the DHCP Server Address is Available go to Auto Install		
12	<p>Log on to the Phone's web portal</p> <p>For example: http://<Phone's IP></p>	A Sign in box is displayed
13	<p>Enter the Username: admin</p> <p>Enter the Password: 22222</p> <p>Click OK or Sign in</p>	The Mitel System Information page is displayed.
14	Select Configuration Server on the navigation tree.	The Configuration Server Setting page is displayed. The Download Protocol displayed is TFTP.
15	Select HTTPS from the Download Protocol drop-down list	The HTTPS options are enabled.
16	<p>Enter the HTTPS server.</p> <p>For example: tb20xsp.cslab.mitel.com</p> <p>Enter the HTTPS Path.</p> <p>For example: dms/clearspan</p> <p>Enter the HTTPS Port, if needed.</p> <p>For example: 443</p> <p>Click Save Settings.</p>	The Provisioning Complete message is displayed.
17	Select Reset from the Navigation tree.	The Reset page is displayed.
18	Press the Restart button.	A confirmation box is displayed.
19	Click OK .	The Phone will restart.

		The Auto Install screen is displayed.
AUTO INSTALL		
20	<p>Enter the Phone's Auto Install ID.</p> <p>Press Done or use the Navigation/Select Keys to select Enter.</p>	The Confirm User screen is displayed.
21	If the User is correct, Press OK , or use the Navigation/Select keys to select Done.	<p>The Phone Restarts a few times.</p> <p>The correct configuration is displayed on the phone</p>

ADDITIONAL PROCEDURES




The following table lists the additional procedures for restarting a phone, and factory defaulting a phone:


RESTARTING PHONES

	ACTION	EXPECTED RESULTS
Restart Mitel 6863i and 6865i		
1	Press the Option Key. 	The Options List is displayed.
2	Using the Navigation/Select Keys,  scroll down to Restart Phone. Select Enter .	The following message is displayed: Restart Phone? Cancel # Confirm
3	Press # key to restart the phone	The phone will restart.
Restart Mitel 6867i, 6869i, 6920 and 6930		
4	Press the Option Key. 	The Settings screen is displayed. The status is hi-lighted.
5	Scroll to Restart. Press Select .	A Restart Phone box is displayed with the following message: Restart Phone? Yes No
6	Select Yes .	The Phone will restart.
Restart Mitel 6873i and 6940		
7	Press the Option Key. 	The Settings screen is displayed.
8	Swipe the second page, if required.	A Restart Phone box is displayed with the following message:

	Touch the Restart icon.	Restart Phone? Yes No
9	Touch Yes.	The phone will restart.

FACTORY DEFAULTING PHONES

Factory Default Mitel 6863i and 6865i		
1	<p>Press the Option Key.</p> 	The Options List is displayed.
2	<p>Using the Navigation/Select keys,</p>  <p>scroll down to the Admin Menu. Select the Admin Menu option.</p>	The Admin Password page is displayed.
4	Enter the Admin Password.	The Admin Menu is displayed.
3	Scroll down to Factory Default and select the option.	The Phone displays: RestoreDefaults?
4	Select Yes .	The Phone will Restart.
Factory Default Mitel 6867i, 6869i, 6920 and 6930 Phones		
1	<p>Press the Option Key.</p> 	<p>The Settings screen is displayed.</p> <p>The Status is highlighted.</p>
2	Press the Advanced key.	Enter Administrator Password page in the Advanced Settings page.
3	<p>Enter the Admin Password.</p> <p>Press the Enter key.</p> <p>Scroll right to Reset.</p> <p>Press the Select key.</p>	<p>The Reset page is displayed with two options:</p> <ul style="list-style-type: none"> • Factory Default? • Erase Local Cfg.
4	Select Factory Default, if necessary.	<p>A Reset box is displayed with the following message:</p> <p>Factory Default</p>

		Yes No
5	Select Yes .	The Phone Restarts.
Factory Default Mitel 6873i and 6940 Phones		
1	<p>Press the Option Key.</p> 	The Settings screen is displayed.
2	Touch Advanced .	Enter Administrator Password in the Advanced Settings page.
3	<p>Enter the Admin Password.</p> <p>Touch the Enter symbol.</p> <p>Swipe the screen to display the next page where Reset is displayed, if required.</p> <p>Touch Reset.</p>	<p>The Reset page is displayed with two options:</p> <ul style="list-style-type: none"> • Factory Default • Erase Local Cfg.
4	<p>Select Factory Default, if necessary.</p> <p>Touch Select.</p>	<p>The Reset box is displayed with the following message:</p> <p>Factory Default</p> <p>Yes No</p>
5	Touch Yes .	The Phone Restarts.

This document contains sensitive and proprietary information and company trade secrets that are critical to Clearspan business. This information may not be disclosed to any person or party without the express written consent of Clearspan. This document may not be reproduced in full or in part without the express permission of an officer or director of Clearspan.